



Without offset

Right hand (R) shown

Cat. No.	Stock		Dimensions (mm)						Standard corner radius r_{Σ}	Applicable inserts	Parts		Torque (N·m)
	R	L	h	b	L ₁	L ₂	h ₁	f			Clamping screw	Wrench	
JSVABR/L1010K11	●	●	10	10	125	21	10	10	0.2	VB□□1103	CSTB-2.5	T-8F	1.2
JSVABR/L1212K11	●	●	12	12	125	21	12	12	0.2				
JSVABR/L1616K11	●	●	16	16	125	21	16	16	0.2				

Basic Selection Chipbreakers VB□□1103

Operation	Precision finishing	Finishing	Finishing to medium cutting	Finishing to medium cutting	Finishing to medium cutting	Finishing to medium cutting	Cast Iron	Aluminium alloy	Hard materials
Chipbreaker	JS	PSF	J10	FR/L-J10	PS	PSS	CM	J10	T-CBN
Page	2-134	2-133	2-134	2-134	2-133	2-133	2-133	2-134	3-13
Appearance									
Toolholders			Sharp edges						
JSV**11	VBGT1103**	VBMT1103**	VBGT1103**	VBGT1103**	VBMT1103**	VBMT1103**	VBGT1103**	VBGT1103**	2QP-VBGW1103**

● : Stocked items.